



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 14

LOCTITE SF 7063 known as Loctite 7063

SDS No. : 229602
V006.0

Revision: 26.07.2019
printing date: 22.12.2020

Replaces version from: 06.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7063 known as Loctite 7063

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Solvent based cleaner

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000
Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|---|------------|
| Flammable liquids | Category 2 |
| H225 Highly flammable liquid and vapor. | |
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H336 May cause drowsiness or dizziness. | |
| Target organ: Central nervous system | |
| Chronic hazards to the aquatic environment | Category 2 |
| H411 Toxic to aquatic life with long lasting effects. | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Naphtha, hydrotreated light, <0,1% benzene

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:

For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapors.
 P273 Avoid release to the environment.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of water.

**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Solvent cleaner

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|--|-------------------------------|-----------|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | 265-151-9 | 50- 100 % | Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411 |
| Ethanol 64-17-5 | 200-578-6 01-2119457610-43 | 10- 20 % | Eye Irrit. 2 H319 Flam. Liq. 2 H225 |
| Methylal 109-87-5 | 203-714-2 01-2119664781-31 | 10- 20 % | Flam. Liq. 2 H225 |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.
Declaration of ingredients according to Detergent Regulation 648/2004/EC**

> 30 % aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.
 Store in a partly filled, closed container until disposal.
 Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep away from sources of ignition - no smoking.
 Vapours should be extracted to avoid inhalation.
 Use only in well-ventilated areas.
 Avoid skin and eye contact.
 See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.
 Do not eat, drink or smoke while working.
 Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.
 Do not store near sources of heat or ignition, or reactive materials.
 Refer to Technical Data Sheet

7.3. Specific end use(s)

Solvent based cleaner

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
 Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-------|-------------------|-----------------------------------|--|-----------------|
| Ethanol 64-17-5 [ETHANOL] | 1.000 | 1.920 | Time Weighted Average (TWA): | | EH40 WEL |
| Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE] | 1.250 | 3.950 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE] | 1.000 | 3.160 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
 Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-------|-------------------|-----------------------------------|--|-----------------|
| Ethanol 64-17-5 [ETHANOL] | 1.000 | | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| Dimethoxymethane 109-87-5 [METHYLAL] | 1.000 | 3.100 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---------------------------|------------------------------|-----------------|-------------|-----|--------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Ethanol 64-17-5 | aqua (freshwater) | | 0,96 mg/l | | | | |
| Ethanol 64-17-5 | aqua (marine water) | | 0,79 mg/l | | | | |
| Ethanol 64-17-5 | aqua (intermittent releases) | | 2,75 mg/l | | | | |
| Ethanol 64-17-5 | sewage treatment plant (STP) | | 580 mg/l | | | | |
| Ethanol 64-17-5 | sediment (freshwater) | | | | 3,6 mg/kg | | |
| Ethanol 64-17-5 | sediment (marine water) | | | | 2,9 mg/kg | | |
| Ethanol 64-17-5 | Soil | | | | 0,63 mg/kg | | |
| Ethanol 64-17-5 | oral | | | | 380 mg/kg | | |
| Dimethoxymethane 109-87-5 | aqua (freshwater) | | 14,577 mg/l | | | | |
| Dimethoxymethane 109-87-5 | aqua (marine water) | | 1,4577 mg/l | | | | |
| Dimethoxymethane 109-87-5 | sediment (freshwater) | | | | 13,135 mg/kg | | |
| Dimethoxymethane 109-87-5 | sediment (marine water) | | | | 1,3135 mg/kg | | |
| Dimethoxymethane 109-87-5 | Soil | | | | 4,6538 mg/kg | | |
| Dimethoxymethane 109-87-5 | Sewage treatment plant | | 10000 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|-----------------|--------------------|-------------------|---------------------------------------|---------------|-----------|---------|
| Ethanol 64-17-5 | Workers | dermal | Long term exposure - systemic effects | | 343 mg/kg | |
| Ethanol 64-17-5 | Workers | inhalation | Long term exposure - systemic effects | | 950 mg/m3 | |
| Ethanol 64-17-5 | General population | dermal | Long term exposure - systemic effects | | 206 mg/kg | |
| Ethanol 64-17-5 | General population | inhalation | Long term exposure - systemic effects | | 114 mg/m3 | |
| Ethanol 64-17-5 | General population | oral | Long term exposure - systemic effects | | 87 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Ensure adequate ventilation.

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Appearance | liquid colourless |
| Odour threshold | No data available / Not applicable |
| pH | Not applicable |
| Melting point | No data available / Not applicable |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | 45 °C (113 °F) |
| Flash point | -18 °C (0.4 °F) |
| Evaporation rate | Not available. |
| Flammability | No data available / Not applicable |
| Explosive limits | |
| lower | 0,8 % (V) |
| upper | 15 % (V) |
| Vapour pressure (20 °C (68 °F)) | 440 hPa |
| Relative vapour density: | Not available. |
| Density (20 °C (68 °F)) | 0,749 g/cm ³ |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Insoluble |
| Solubility (qualitative) (Solvent: Acetone) | Miscible |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |

| | |
|---------------------------|------------------------------------|
| Decomposition temperature | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

| | |
|----------------------|-----------------|
| Ignition temperature | 200 °C (392 °F) |
|----------------------|-----------------|

SECTION 10: Stability and reactivity**10.1. Reactivity**

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information**General toxicological information:**

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Ethanol 64-17-5 | LD50 | 10.470 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Methylal 109-87-5 | LD50 | 6.423 mg/kg | rat | not specified |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Ethanol 64-17-5 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Methylal 109-87-5 | LD50 | > 5.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---|------------|-------------|-----------------|---------------|---------|---|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | LC50 | > 5,61 mg/l | dust/mist | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| Ethanol 64-17-5 | LC50 | 124,7 mg/l | vapour | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Methylal 109-87-5 | LC50 | 15.000 mg/l | vapour | 4 h | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|----------------|---------------|---------|--|
| Ethanol 64-17-5 | not irritating | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|----------------|---------------|---------|---|
| Ethanol 64-17-5 | irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Ethanol 64-17-5 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|------------------------------|-----------------|------------------------------------|------------|---|
| Ethanol 64-17-5 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Ethanol 64-17-5 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|------------------------------|----------|--|--------------------------------------|---------|--|
| Ethanol 64-17-5 | negative | bacterial reverse mutation assay (e.g Ames test) | | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Ethanol 64-17-5 | negative | in vitro mammalian chromosome aberration test | without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Ethanol 64-17-5 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---------------------------------|--------|-------------------------|---|---------|--------|---------------|
| Ethanol 64-17-5 | | oral: unspecified | | rat | | not specified |
| Ethanol 64-17-5 | | dermal | | mouse | female | not specified |
| Ethanol 64-17-5 | | inhalation | | mouse | male | not specified |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---------------------------------|----------------------|----------------------------|-------------------------|---------|--|
| Ethanol 64-17-5 | NOAEL P 13.800 mg/kg | Two generation study | oral: unspecified | mouse | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-------------|---------------|---------------------|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | LL50 | 8,2 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Ethanol 64-17-5 | LC50 | 14.200 mg/l | 96 h | Pimephales promelas | EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians) |
| Ethanol 64-17-5 | NOEC | 250 mg/l | 120 h | Danio rerio | OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages) |
| Methylal 109-87-5 | LC50 | 6.990 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|--------------------|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | EL50 | 4,5 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Ethanol 64-17-5 | EC50 | 5.012 mg/l | 48 h | Ceriodaphnia dubia | other guideline: |
| Methylal 109-87-5 | EC50 | > 500 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|----------|---------------|---------------|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | NOELR | 2,6 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Ethanol 64-17-5 | NOEC | 9,6 mg/l | 9 d | Daphnia magna | not specified |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | EL50 | 3,1 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | NOELR | 0,5 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Ethanol 64-17-5 | EC50 | 275 mg/l | 72 h | Chlorella vulgaris | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Ethanol 64-17-5 | EC10 | 11,5 mg/l | 72 h | Chlorella vulgaris | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Methylal 109-87-5 | EC10 | > 500 mg/l | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|--------------|---------------|------------------|--|
| Ethanol 64-17-5 | IC50 | > 1.000 mg/l | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Methylal 109-87-5 | EC10 | 3.000 mg/l | 17 h | | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test) |

12.2. Persistence and degradability

The product is not biodegradable.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|-----------------------|-----------|---------------|------------------|---|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | readily biodegradable | aerobic | 77,05 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Ethanol 64-17-5 | readily biodegradable | aerobic | 80 - 85 % | 30 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Methylal 109-87-5 | | | 88 % | 30 d | OECD 301 A - F |

12.3. Bioaccumulative potential

No data available.

No substance data available.

12.4. Mobility in soil

The product evaporates readily.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|---------|-------------|---|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | 4 - 5,7 | | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Ethanol 64-17-5 | -0,35 | 24 °C | not specified |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|--|
| Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Ethanol 64-17-5 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of according to regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

| | |
|------|------|
| ADR | 1993 |
| RID | 1993 |
| ADN | 1993 |
| IMDG | 1993 |
| IATA | 1993 |

14.2. UN proper shipping name

| | |
|------|---|
| ADR | FLAMMABLE LIQUID, N.O.S. (Solvent naphtha,Dimethoxymethane) |
| RID | FLAMMABLE LIQUID, N.O.S. (Solvent naphtha,Dimethoxymethane) |
| ADN | FLAMMABLE LIQUID, N.O.S. (Solvent naphtha,Dimethoxymethane) |
| IMDG | FLAMMABLE LIQUID, N.O.S. (Solvent naphtha,Dimethoxymethane) |
| IATA | Flammable liquid, n.o.s. (Solvent naphtha,Dimethoxymethane) |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 3 |
| RID | 3 |
| ADN | 3 |
| IMDG | 3 |
| IATA | 3 |

14.4. Packing group

| | |
|------|----|
| ADR | II |
| RID | II |
| ADN | II |
| IMDG | II |
| IATA | II |

14.5. Environmental hazards

| | |
|------|---------------------------|
| ADR | Environmentally Hazardous |
| RID | Environmentally Hazardous |
| ADN | Environmentally Hazardous |
| IMDG | Marine pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|---|
| ADR | Special provision 640D Tunnelcode: (D/E) |
| RID | Special provision 640D |
| ADN | Special provision 640D |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 100 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.