

LICA 2



Grease



Multipurpose Lithium/Calcium grease

APPLICATION

Multipurpose grease

General Lubrication

- 1 It is a multipurpose grease, recommended for the lubrication of the bearings and all mechanical parts in the temperature range -30 to 110°C
- 1 Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

SPECIFICATIONS

International Specification

- 1 ISO 6743-9: L-XCCEA2; DIN 51502: K2H-30

ADVANTAGES

Mechanical stability Thermal stability

- 1 Multipurpose grease
- 1 Miscible with the most other conventional soap greases
- 1 Good mechanical stability
- 1 Good thermal stability

CARACTERISTICS	METHODS	UNITS	LICA 2
NLGI Class	ASTM D 217	-	2
Soap/thickener		-	Lithium/Calcium
Appearance	Visual	-	Smooth
Color	Visual	-	Pale-brown
Dropping point	ASTM D 2265	°C	>170
Penetration at 25°C	ASTM D 217	0.1 mm	265 - 295

Above characteristics are mean values given as information.

TOTAL Marketing Middle East
United Arab Emirates
Dubai

LICA 2
N° TDS/DXB/16/01/444

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available at www.quickfds.com