

MARTOL LVG 15 CF



Metalworking



Pressing oil evanescent fluid.

APPLICATIONS

- Fine pressing of aluminium (0.5 mm).

ADVANTAGES

- Colourless and odorless mineral oil.
- Does not contain Chlorine.
- Excellent wettability on aluminium.
- Lubricity doping give improved tool edge retention and extremely good surface finish - factors which all contribute towards reduced production costs.
- Residue < 0.05 % m/m after passage through stove at 200°C for two hours.
- Does not stain the aluminium.
- This oil contains selected petroleum bases and additives designed to guarantee: - residue < 0.05 % by mass,
 - excellent wettability on aluminium,
 - no marks on aluminium during heat treatment of aluminium.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL LVG 15 CF
Appearance	Visual	-	clear liquid
Density at 15°C	ISO 3675	kg/m ³	765
Colour	Visual	-	colourless
Viscosity at 20°C	ISO 3104	mm ² /s	1.8
PM Flash point	ISO 2719	°C	> 60

The characteristics shown in this table are typical values given for illustrative purposes.

**TOTAL LUBRIFIANTS
INDUSTRIE**

08-02-2017 (annule et remplace version du 16-09-2003)

MARTOL LVG 15 CF

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.