

# MARTOL LVG 25 CF



*Metalworking*



## UTILISATIONS

- **MARTOL LVG 25** is an evaporating oil for low and medium severe drawing on steel and non-iron metals.
- **MARTOL LVG 25** can be applied with a brush by spraying or with a roller.

## ADVANTAGES

- **MARTOL LVG 25 CF** is characterised by:
  - His evaporating character
  - A good wetability of the lubricant which assure an excellent surface covering
  - Can be used in certain cases on coated metal
  - Leaves a thin film and degreasing operation is most of the time unnecessary.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL LVG 25 CF
Density at 15°C	ISO 12185	Kg/l	0.774
Viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	1.75
Pour point	NFT 60-105	°C	-12
Flash point (PM)	ISO 2719	°C	74
TAN	ASTM D 664	mg KOH/g	0.13

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS  
INDUSTRIE**

16-04-2013 (supersedes 27-07-2001)

MARTOL LVG 25 CF

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).