

# OSYRIS DWX 7000



*Metalworking*

## UTILISATIONS

- **OSYRIS DWX 7000** is a dewatering and protective fluid.
- In addition, **OSYRIS DWX 7000** coats the surface with a fatty soft film to give a long-term protection during outdoor sheltered storage.
- **OSYRIS DWX 7000** complies with standard ISO 6743/8 (1987) : REE category.

## ADVANTAGES

- **OSYRIS DWX 7000** is widely recommended for use the metal industry or after a surface treatment.
- Good water-repellent capability.
- **OSYRIS DWX 7000** deposits a fatty soft protective film.
- Protection guaranteed during 18 months in case of indoor storage and 12 months in case of outdoor storage under rain-shelter.
- **OSYRIS DWX 7000** may be applied:
  - by dipping,
  - by spraying,
  - by brushing.
  - The film may be eliminated by:
    - alkaline detergent
    - solvents (liquid or vapour phase).

TYPICAL CHARACTERISTICS	METHODS	UNITS	OSYRIS DWX 7000
Appearance	visual	-	liquid
Colour	visual	-	Dark red
Specific gravity at 15 °C	ISO 3675	kg/dm <sup>3</sup>	0.850
Kinematic viscosity at 20 °C	ISO 3104	mm <sup>2</sup> /s	10
Kinematic viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	6
Flash point	ISO 2719	°C	38
Pour point	ISO 3016	°C	- 20
Water displacement power	IP 178 (B)	value	yes

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS**  
**Industrie & Spécialités**

27 august 2001

OSYRIS DWX 7000

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

[www.quick-fds.com](http://www.quick-fds.com).

