

OSYRIS DWY 5500



Metalworking

Barium-free dewatering fluid with temporary anti-corrosion effect. Water or watery solutions are displaced reliably.

UTILISATIONS

- Preserving of bright, polished and ground machine parts. **OSYRIS DWY 5500** can be applied by plunging, with a brush or a sponge. The protective film can be removed with slightly alkaline detergents, liquid solvents or solvents brought mechanically into vapour phase.

TYPICAL CHARACTERISTICS	METHODS	UNITS	OSYRIS DWY 5500
Colour	DIN ISO 2049	-	2,0
Appearance	-	-	clear
Density at 15°C	ISO 3675	kg/dm ³	0.823
Viscosity at 20 °C	ISO 3104	mm ² /s	3.0
Flash point	ISO 2719	°C	67
Danger class	ISO 2719	-	67
Type of film	-	-	oily, light, not fast to handling
Film strength	µm	-	1.5
Evaporation time of the solvent	h	-	2 - 3

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

13 september 2001

OSYRIS DWY 5500

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

