

Mobil Velocite Oil Numbered Series

Spindle and Hydraulic Oils

Product Description

The Mobil Velocite Oil Numbered Series oils are premium performance products primarily designed for the lubrication of high-speed spindles in machine tools. They are also used in some critical hydraulic, circulation systems and air line oilers where the appropriate viscosity grade is selected. They are formulated from select high-quality, low viscosity base oils and additives that impart good resistance to oxidation and protection from rust and corrosion. They possess very good resistance to foaming and separate readily from water.

Features and Benefits

The Mobil Velocite Oil Numbered Series provide exceptional lubrication of close-tolerance bearings which helps keep the bearings running cool and helps maintain the precision required by many of today's critical machine tools. Although the Mobil Velocite Oil Numbered Series oils were designed for spindle bearings, they exhibit the required properties to function as low pressure hydraulic and circulating oils as long as the proper viscosity is selected. This feature can help minimise inventory costs and reduce the potential for product misapplication.

Features	Advantages and Potential Benefits
Good Oxidation Resistance	Helps reduce critical deposit formationImproves oil life
Very Good Rust and Corrosion Protection	Improves equipment lifeProvides increased precision long-term
Effective Water Separation	Resists emulsion formationKeeps moisture out of critical lubrication areasAllows easy removal of moisture from system reservoirs

Applications

- High speed spindle bearings in machine tools and equipment where high speeds and fine clearances are involved
- Precision grinders, lathes, jig borers and tracer mechanisms
- Velocite Oil No 3 is recommended for "zero clearance" type spindle bearings which operate with extremely close clearances
- For sleeve type spindle bearings having greater clearances, the choice of viscosity depends on the relation between clearance and spindle speed
- Low pressure hydraulic systems where appropriate viscosity is selected
- Air line oilers (Mobil Velocite Oil No. 10)
- For some sensitive instruments such as telescopes, laboratory equipment, etc.



Specifications and Approvals

Mobil Velocite Oil Numbered Series meets or exceeds the following industry specifications:	No 3	No 4	No 6	No 8	No 10
Cincinnati Machine P-65	X				
Cincinnati Machine P-62			X		
Cincinnati Machine P-45					X

Typical Properties

Mobil Velocite Oil Numbered Series	No 3	No 4	No 6	No 8	No 10
ISO VG	2		10	15	22
Viscosity, ASTM D 445					
cSt @ 40°C	2.1	4.83	10.0	15.0	22.0
cSt @ 100°C	0.95	1.53	2.62	3.28	4.0
Total Acid Number, ASTM D 974, mgKOH/g	0.06	0.06	0.06	0.06	0.1
Copper Strip Corrosion, 3 hrs @ 100° C, ASTM D 130	1A	1A	1A	1A	1A
Rust Characteristics, Proc A, ASTM D 665	Pass	Pass	Pass	Pass	Pass
Pour Point, °C, ASTM D 97	-36	-15	-15	-9	-30
Flash Point, °C, ASTM D 92	84	102	180	194	212
Density @ 15° C, ASTM D 4052, kg/L	0.802	0.822	0.844	0.854	0.862

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Velocite are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.