

Product Description

Anglomoil WO Gear Oils are made from Paraffinic white Oils and special additive packages and are NFS H-1 listed for use where incidental food contact can occur.

Product Features & Benefits

Anglomoil WO Gear Oils are recommended for gear sets, bearings, circulating oil systems and chain applications in food processing machinery.

Anglomoil WO Gear Oil is formulated from Paraffinic white Oils and have good thermal stability and lubricity. This high performance is further enhanced by Anglomoil's unique additive system.

Anglomoil WO Gear oils will provide:

- Good service life.
- Longer life with fewer oil changes,
- Extended equipment life
- Reduced energy costs
- Good high and low temperature operations
- Good oxidative stability

Compatibility

Anglomoil white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an Anglomoil white oil hydrocarbon-based lubricant.

Typical Characteristics

	Method	ISO 100	ISO 220
S.G. @ 20 °C	ASTM D4052	0.876	0.881
Viscosity @ 40°C	ASTM D445	100	220
Viscosity @ 100°C	ASTM D445	11.7	19.7
Viscosity Index	ASTM D2270	105	102

Master Item# 2479 & 2481
 Pack Size Availability: 20L

Last Updated: 26th July 2021